

Tremendous Power and Toughness



PRESTIGE

SPECIFICATIONS

Model	Prestige BS-III	Prestige BS-IV
Engine & Displacement	SLT3 & Numeral, 3455 cc	SLT4 & Numeral, 3455 cc
Type	4-Cylinder in line -OHV	Comman Rail Cool EGR
	Diesel Turbo Charger with Intercooler	
Max.Engine Output	75 Kw @3000 rpm	75 Kw @2800 rpm
Max. Torque	270Nm@1750-2000 rpm	296Nm @ 1500 rpm
Clutch	Single plate Diaphragm Type, Dia. 260mm	
Gear Box	Synchromesh Manual 5-Forward and 1-Reverse	
Steering	Mechanical /Power Steering (Optional)	
Brakes	Hydraulic Vaccum assisted	
Suspension	Semi Elliptical Type Multi Leaf Spring	
Wheels & Tyres	7.50" X 16" - 14 PR/16 PR	
No of Tyres	6+1	
Wheelbase (mm)	2815	3335
Min. Turning Circle Diameter in m	5.5	6.4
Max. Permissible GVW (kg)	6440	6440
Front Axle Weight	2380	2380
Rear Axle Weight	4080	4080
Kerb Weight	3090	3100
Cargo Box Dimensions (LXBXH) in mm		
Variants		
Cab Halfdeck Loadbody	3100 X 2080 X 2070	3100 X 2080 X 2070
Cab Semideck Loadbody	3100 X 2080 X 2092	3100 X 2080 X 2092
Cab Highdeck Loadbody	3100 X 2080 X 2710	3100 X 2080 X 2710
Cabin Chassis	Available	

NOTE : As our policy is that of continuous improvement, above specifications may change without notice.

SML ISUZU Limited

S.C.O. 204 - 205, Sector 34-A,
Chandigarh - 160 135.
Ph : 0172-2647700. Fax : 0172-2615111.
E-mail : salesadm@smlisuzu.com

Authorised Dealer :

12/2011

**SML
ISUZU**

Features

- Available in BS - III & BS - IV Versions.
- Powerful Engine - Higher Pickup, Higher Torque at lower RPM, Gradeability and Fuel Efficiency.
- Heavy Duty Gear Box and Bigger Clutch - Longer Life.
- Box Type Chassis with tubular cross members - carry more load, provide better Strength and Rigidity.
- Steering with variable Gear Ratio - Less Driver Fatigue.
- Roof Ventilation, less Driver Fatigue and Better Comfort.
- Ready availability of Spares at reasonable Price.

