

Engineered on **Doctor's** Advice...



Ambulance

SPECIFICATIONS

Model	Ambulance BS-III	Ambulance BS-IV
Engine & Displacement	SLT3 & Numeral, 3455 cc	SLT4 & Numeral , 3455 cc
Type	4-Cylinder in line -OHV	Comman Rail Cool EGR
	Diesel Turbo Charger with Intercooler	
Max.Engine Output	75 Kw @3000 rpm	75 Kw @2800 rpm
Max. Torque	270Nm@1750-2000 rpm	296Nm @ 1500 rpm
Clutch	Single plate Diaphragm Type , Dia. 260mm	
Gear Box	Synchromesh Manual 5-Forward and 1-Reverse	
Steering	Mechanical /Power Steering (Optional)	
Brakes	Hydraulic Vaccume assisted	
Suspension	Semi Elliptical Type Multi Leaf Spring	
Min. Ground Clearance (mm)	206	
Wheels & Tyres	7.50" X 16" - 14PR/16 PR	
No of Tyres	6+1	4+1
Wheelbase (mm)	2515	2815
Min. Turning Circle Diameter in m	5	5.5
Front Axle Weight	2400	2580
Rear Axle Weight	3800	3160
Max. Permissible GVW (kg)	5740	6200
Fuel Capacity (Its)	90	
Dimensions (LXBXH) in mm		
Overall Length	4919	5479
Overall Width	2100	2100
Overall Height	2725	2725
Optional Fitments	Air Conditioning	

NOTE : As our policy is that of continuous improvement, above specifications may change without notice.

SML ISUZU Limited

S.C.O. 204 - 205, Sector 34-A,
Chandigarh - 160 135.
Ph : 0172-2647700. Fax : 0172-2615111.
E-mail : salesadm@smlisuzu.com

Authorised Dealer :

SML ISUZU

Features

- ◆ Soft suspension provides quides quite and comfortable ride.
- ◆ Infection carrying items such as spare tyres are housed outside patients compartment.
- ◆ Full standing height for movement of Doctors/ attendants with comfortable seating arrangements.

