

**BUILT STRONGER**  
**to EARN MORE**



**TIPPER**

# SPECIFICATIONS

Model	Tipper BS-III				Tipper BS-IV		
Engine & Displacement	SLT3 & Numeral , 3455 cc				SLT4 & Numeral , 3455 cc		
Type	4-Cylinder in line -OHV				Comman Rail Cool EGR		
	Diesel Turbo Charger with Intercooler						
Max.Engine Output	75 Kw @3000 rpm				75 Kw @2800 rpm		
Max. Torque	270Nm@1750-2000 rpm				296Nm @ 1500 rpm		
Clutch	Single plate Diaphragm Type , Dia. 260mm						
Gear Box	Synchromesh Manual 5-Forward and 1-Reverse						
Steering	Mechanical /Power Steering (Optional)						
Brakes	Hydraulic Vaccume assisted				Air Brake		
Suspension	Semi Elliptical Type Multi Leaf Spring						
No of Tyres	6+1						
Wheels & Tyres	7.50" X 16" -14PR/16 PR				8.25" X 16" -16 PR	7.50" X 16" -14PR/16 PR	
Model	WT49ES-Prestige	WT49TC-Prestige	ZT54ES-Supreme	ZT54ES-Supreme	ZT54SM-Samrat	ZT54AB-Super AB	ZT54AB-Super AB
Wheelbase (mm)	2815	3335	2815	3335	3335	3335	2815
Min. Turning Circle Diameter in m	5.5	6.4	5.5	6.4	6.4	6.4	5.5
Front Axle Weight	2360	2360	2800	2800	3370	3160	3160
Rear Axle Weight	4080	4080	5200	5200	6880	5560	5560
Kerb Weight	2550	3100	2800	2800	3100	3150	3310
Max. Permissible GVW (kg)	6440	6440	8000	8000	10250	8720	8720
Body and Tipping System							
Body Capacity (Cu.Mtr)	3.5	4	4	4	5.5	4.5	4
Height (mm)	460	500	500	500	625	500	500
Tipping Angle (Degree)	45	45	45	45	45	45	45
Hydraulic Cylinder (No's)	1	2	2	2	2	2	2



## SML ISUZU Limited

S.C.O. 204 - 205, Sector 34-A,  
Chandigarh - 160 135.  
Ph : 0172-2647700. Fax : 0172-2615111.  
E-mail : salesadm@smlisuzu.com

Authorised Dealer :



12/2011