

Full Filling Wishes



WISH-ECCO Bus

SPECIFICATIONS

Model	Wish Eco Bus BS-III		Wish Eco Bus BS-IV				
Engine & Displacement	SLT3 & Numeral, 3455 cc		SLT4 & Numeral, 3455 cc				
Type	4-Cylinder in line -OHV		Comman Rail Cool EGR				
	Diesel Turbo Charger with Intercooler						
Max.Engine Output	75 Kw @3000 rpm		75 Kw @2800 rpm				
Max. Torque	270Nm@1750-2000 rpm		296Nm @ 1500 rpm				
Clutch	Single plate Diaphragm Type , Dia. 260mm						
Gear Box	Synchromesh Manual 5-Forward and 1-Reverse						
Steering	Mechanical /Power Steering (Optional)						
Brakes	Hydraulic Vaccume assisted / Air Brake (Available only on 50A, 50L and XL Models)						
Suspension	Semi Elliptical Type Multi Leaf Spring						
Variants	48D	26D	48ESD	26SD	50A	50L	XL
Standard Seats	18	20	20	24	26	32	40
High Back Seats	18	20	20	24	26	32	40
Semi-Deluxe Seats	14	16	16	18	20	23	31
Deluxe Seats	10	13	13	14	16	19	23
Dimensions							
Wheelbase (mm)	2515	2815	2815	3335	3335	3940	4760
Overall Length (mm)	4992	5548	5548	6047	6380	7348	8660
Rear Overhang (mm)	1433	1689	1689	1668	2001	2364	2856
Front Overhang (mm)	1044	1044	1044	1044	1044	1044	1044
Wheels & Tyres	7.50 x 16 - 14 PR /16 PR	7.50 x 16 - 14 PR /16 PR	7.50 x 16 - 14 PR /16 PR	8.25 x 16 - 16PR	7.50 x 16 - 14 PR /16 PR / 8.25 x 16 - 16PR	7.50 x 16 - 14 PR /16 PR / 8.25 x 16 - 16PR	7.50 x 16 - 14 PR /16 PR / 8.25 x 16 - 16PR
No of Tyres	6+1	4+1	6+1	4+1	6+1	6+1	6+1
Min. Turning Circle Diameter in m	5.5	5.5	5.5	6.4	6.4	7.6	9.4
Max. Permissible GVW (kg)	6200	5740	6200	5990	6440	6440	8000
GVW (kgs)	6200	5740	6200	5990	6440	6440	8000

NOTE : As our policy is that of continuous improvement, above specifications may change without notice.

SML ISUZU Limited

S.C.O. 204 - 205, Sector 34-A,
Chandigarh - 160 135.
Ph : 0172-2647700. Fax : 0172-2615111.
E-mail : salesadm@smlisuzu.com

Authorised Dealer :



OPTIONAL FEATURES AT EXTRA COST

- ◆ Aluminium Floor ◆ Roof Luggage Carrier
- ◆ Tinted Glasses ◆ Curtain/Curtain Rails
- ◆ Fans ◆ Music System
- ◆ Air Conditioned ◆ Hard Roof.