

The **ICU** on Wheel with Engineering



Cardiac Ambulance

SPECIFICATIONS

Model	Cardiac Ambulance BS-III	Cardiac Ambulance BS-IV
Engine & Displacement	SLT3 & Numeral, 3455 cc	SLT4 & Numeral , 3455 cc
Type	4-Cylinder in line -OHV	Comman Rail Cool EGR
	Diesel Turbo Charger with Intercooler	
Max.Engine Output	75 Kw @3000 rpm	75 Kw @2800 rpm
Max. Torque	270Nm@1750-2000 rpm	296Nm @ 1500 rpm
Clutch	Single plate Diaphragm Type , Dia. 260mm	
Gear Box	Synchronmesh Manual 5-Forward and 1-Reverse	
Steering	Mechanical /Power Steering (Optional)	
Brakes	Hydraulic Vaccume assisted	
Suspension	Semi Ellipitical Type Multi Leaf Spring	
Min. Ground Clearance (mm)	206	
Wheels & Tyres	7.50" X 16" - 14PR/16 PR	8.25" X 16" - 16 PR
No of Tyres	6+1	4+1
Wheelbase (mm)	3335	3335
Min. Turning Circle Diameter in m	6.4	6.4
Front Axle Weight	2360	2400
Rear Axle Weight	4080	3590
Max. Permissible GVW (kg)	6440	5990
Fuel Capacity (Its)	90	
Dimensions (LXBXH) in mm		
Overall Length	5479	5479
Overall Width	2100	2100
Overall Height	2725	2725

NOTE : As our policy is that of continuous improvement, above specifications may change without notice.

Features

- ◆ Doctor Seats ◆ Attendant Seat with storage space ◆ Complete FRP Interior ◆ First Aid Kit
- ◆ Oxygen Suppy system with 2 no's outlet ◆ Invertor 800 VA ◆ Anti acidic stain free vinyl floor
- ◆ Rear Flood Light ◆ Fire Extinguisher ◆ Wash Basin ◆ Foldable stretcher cum trolley
- ◆ P.A system ◆ Provision for drinking water ◆ Bar light & Side blinkers ◆ Tube & Focus Lights in Patient Compartment on AC & DC Supply ◆ Electrical provision for AC/DC Supply (220 V / 12 V)



**SML
ISUZU**

SML ISUZU Limited

S.C.O. 204 - 205, Sector 34-A,
Chandigarh - 160 135.

Ph : 0172-2647700. Fax : 0172-2615111.

E-mail : salesadm@smlisuzu.com

Authorised Dealer :